

# Rules and Regulations

Federal Register

Vol. 70, No. 250

Friday, December 30, 2005

This section of the FEDERAL REGISTER contains regulatory documents having general applicability and legal effect, most of which are keyed to and codified in the Code of Federal Regulations, which is published under 50 titles pursuant to 44 U.S.C. 1510.

The Code of Federal Regulations is sold by the Superintendent of Documents. Prices of new books are listed in the first FEDERAL REGISTER issue of each week.

## DEPARTMENT OF TRANSPORTATION

### Federal Aviation Administration

#### 14 CFR Part 23

[Docket No. CE237, Special Condition 23-177-SC]

#### Special Conditions; Garmin International, Inc., GFC-700 AFCS on the Mooney M20M and M20R With the G1000 EFIS; Protection of Systems for High Intensity Radiated Fields (HIRF)

**AGENCY:** Federal Aviation Administration (FAA), DOT.

**ACTION:** Final special conditions; request for comments.

**SUMMARY:** These special conditions are issued to Garmin International, Inc., 1200 E 151st St., Olathe, KS 66062, for a Supplemental Type Certificate for the Mooney M20M and M20R. These airplanes will have novel and unusual design features when compared to the state of technology envisaged in the applicable airworthiness standards. These novel and unusual design features include the installation of a digital autopilot, Model GFC-700, manufactured by Garmin International, Inc., for which the applicable regulations do not contain adequate or appropriate airworthiness standards for the protection of these systems from the effects of high intensity radiated fields (HIRF). This system will interface to the G1000 EFIS, which is also covered by these special conditions, which contain the additional safety standards that the Administrator considers necessary to establish a level of safety equivalent to the airworthiness standards applicable to these airplanes.

**DATES:** The effective date of these special conditions is December 21, 2005. Comments must be received on or before January 30, 2006.

**ADDRESSES:** Comments may be mailed in duplicate to: Federal Aviation

Administration, Regional Counsel, ACE-7, Attention: Rules Docket Clerk, Docket No. CE237, Room 506, 901 Locust, Kansas City, Missouri 64106. All comments must be marked: Docket No. CE237. Comments may be inspected in the Rules Docket weekdays, except Federal holidays, between 7:30 a.m. and 4 p.m.

**FOR FURTHER INFORMATION CONTACT:** Wes Ryan, Aerospace Engineer, Standards Office (ACE-110), Small Airplane Directorate, Aircraft Certification Service, Federal Aviation Administration, 901 Locust, Room 301, Kansas City, Missouri 64106; telephone (816) 329-4127.

**SUPPLEMENTARY INFORMATION:** The FAA has determined that notice and opportunity for prior public comment hereon are impracticable because these procedures would significantly delay issuance of the approval design and thus delivery of the affected aircraft. In addition, the substance of these special conditions has been subject to the public comment process in several prior instances with no substantive comments received. The FAA, therefore, finds that good cause exists for making these special conditions effective upon issuance.

#### Comments Invited

Interested persons are invited to submit such written data, views, or arguments, as they may desire. Communications should identify the regulatory docket or notice number and be submitted in duplicate to the address specified above. All communications received on or before the closing date for comments will be considered by the Administrator. The special conditions may be changed in light of the comments received. All comments received will be available in the Rules Docket for examination by interested persons, both before and after the closing date for comments. A report summarizing each substantive public contact with FAA personnel concerning this rulemaking will be filed in the docket. Commenters wishing the FAA to acknowledge receipt of their comments submitted in response to this notice must include a self-addressed, stamped postcard on which the following statement is made: "Comments to Docket No. CE237." The postcard will be date stamped and returned to the commenter.

## Background

On November 1, 2005, Garmin International, Inc., 1200 E 151st St., Olathe, KS 66062, made an application to the FAA for a new Supplemental Type Certificate for the Mooney M20M and M20R. The Mooney M20M and M20R are currently approved under TC No. 2A3. The proposed modification incorporates a novel or unusual design feature, such as digital avionics consisting of a digital autopilot that is vulnerable to HIRF external to the airplane.

## Type Certification Basis

Under the provisions of 14 CFR part 21, § 21.101, Garmin International, Inc. must show that the Mooney M20M and M20R meet their original certification basis, as listed on Type Data Sheet 2A3, the additional certification requirements added for the GGFC-700 system, exemptions, if any; and the special conditions adopted by this rulemaking action. The additional certification requirements for the GFC-700 system and G1000 include 23.1301, 23.1309, 23.1311, 23.1322, 23.1353 and other rules at the amendment appropriate for the date of application. Further details of the certification basis for the installation of the GFC-700 autopilot and G1000 EFIS are available on request.

## Discussion

If the Administrator finds that the applicable airworthiness standards do not contain adequate or appropriate safety standards because of novel or unusual design features of an airplane, special conditions are prescribed under the provisions of § 21.16.

Special conditions, as appropriate, as defined in § 11.19, are issued in accordance with § 11.38 after public notice and become part of the type certification basis in accordance with § 21.101.

Special conditions are initially applicable to the model for which they are issued. Should the applicant apply for a supplemental type certificate to modify any other model already included on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would also apply to the other model under the provisions of § 21.101.

### Novel or Unusual Design Features

Garmin International, Inc., plans to incorporate certain novel and unusual design features into the Mooney M20M and M20R for which the airworthiness standards do not contain adequate or appropriate safety standards for protection from the effects of HIRF. These features include an autopilot, which are susceptible to the HIRF environment, that were not envisaged by the existing regulations for this type of airplane.

*Protection of Systems from High Intensity Radiated Fields (HIRF):* Recent advances in technology have given rise to the application in aircraft designs of advanced electrical and electronic systems that perform functions required for continued safe flight and landing. Due to the use of sensitive solid-state advanced components in analog and digital electronics circuits, these advanced systems are readily responsive to the transient effects of induced electrical current and voltage caused by the HIRF. The HIRF can degrade electronic systems performance by

damaging components or upsetting system functions.

Furthermore, the HIRF environment has undergone a transformation that was not foreseen when the current requirements were developed. Higher energy levels are radiated from transmitters that are used for radar, radio, and television. Also, the number of transmitters has increased significantly. There is also uncertainty concerning the effectiveness of airframe shielding for HIRF. Furthermore, coupling to cockpit-installed equipment through the cockpit window apertures is undefined.

The combined effect of the technological advances in airplane design and the changing environment has resulted in an increased level of vulnerability of electrical and electronic systems required for the continued safe flight and landing of the airplane. Effective measures against the effects of exposure to HIRF must be provided by the design and installation of these systems. The accepted maximum energy levels in which civilian airplane system

installations must be capable of operating safely are based on surveys and analysis of existing radio frequency emitters. These special conditions require that the airplane be evaluated under these energy levels for the protection of the electronic system and its associated wiring harness. These external threat levels, which are lower than previous required values, are believed to represent the worst case to which an airplane would be exposed in the operating environment.

These special conditions require qualification of systems that perform critical functions, as installed in aircraft, to the defined HIRF environment in paragraph 1 or, as an option to a fixed value using laboratory tests, in paragraph 2, as follows:

(1) The applicant may demonstrate that the operation and operational capability of the installed electrical and electronic systems that perform critical functions are not adversely affected when the aircraft is exposed to the HIRF environment defined below:

Frequency	Field strength (volts per meter)	
	Peak	Average
10 kHz–100 kHz .....	50	50
100 kHz–500 kHz .....	50	50
500 kHz–2 MHz .....	50	50
2 MHz–30 MHz .....	100	100
30 MHz–70 MHz .....	50	50
70 MHz–100 MHz .....	50	50
100 MHz–200 MHz .....	100	100
200 MHz–400 MHz .....	100	100
400 MHz–700 MHz .....	700	50
700 MHz–1 GHz .....	700	100
1 GHz–2 GHz .....	2000	200
2 GHz–4 GHz .....	3000	200
4 GHz–6 GHz .....	3000	200
6 GHz–8 GHz .....	1000	200
8 GHz–12 GHz .....	3000	300
12 GHz–18 GHz .....	2000	200
18 GHz–40 GHz .....	600	200

The field strengths are expressed in terms of peak root-mean-square (rms) values.

or,

(2) The applicant may demonstrate by a system test and analysis that the electrical and electronic systems that perform critical functions can withstand a minimum threat of 100 volts per meter, electrical field strength, from 10 kHz to 18 GHz. When using this test to show compliance with the HIRF requirements, no credit is given for signal attenuation due to installation.

A preliminary hazard analysis must be performed by the applicant for approval by the FAA to identify either electrical or electronic systems that perform critical functions. The term “critical” means those functions, whose

failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane. The systems identified by the hazard analysis that perform critical functions are candidates for the application of HIRF requirements. A system may perform both critical and non-critical functions. Primary electronic flight display systems, and their associated components, perform critical functions such as attitude, altitude, and airspeed indication. The HIRF requirements apply only to critical functions.

Compliance with HIRF requirements may be demonstrated by tests, analysis,

models, similarity with existing systems, or any combination of these. Service experience alone is not acceptable since normal flight operations may not include an exposure to the HIRF environment. Reliance on a system with similar design features for redundancy as a means of protection against the effects of external HIRF is generally insufficient since all elements of a redundant system are likely to be exposed to the fields concurrently.

### Applicability

As discussed above, these special conditions are applicable to the Mooney M20M and M20R. Should Garmin

International, Inc., apply at a later date for a supplemental type certificate to modify any other model on the same type certificate to incorporate the same novel or unusual design feature, the special conditions would apply to that model as well under the provisions of § 21.101.

### Conclusion

This action affects only certain novel or unusual design features on one model of airplane. It is not a rule of general applicability and affects only the applicant who applied to the FAA for approval of these features on the airplane.

The substance of these special conditions has been subjected to the notice and comment period in several prior instances and has been derived without substantive change from those previously issued. It is unlikely that prior public comment would result in a significant change from the substance contained herein. For this reason, and because a delay would significantly affect the certification of the airplane, which is imminent, the FAA has determined that prior public notice and comment are unnecessary and impracticable, and good cause exists for adopting these special conditions upon issuance. The FAA is requesting comments to allow interested persons to submit views that may not have been submitted in response to the prior opportunities for comment described above.

### List of Subjects in 14 CFR Part 23

Aircraft, Aviation safety, Signs and symbols.

### Citation

■ The authority citation for these special conditions is as follows:

**Authority:** 49 U.S.C. 106(g), 40113 and 44701; 14 CFR 21.16 and 21.101; and 14 CFR 11.38 and 11.19.

### The Special Conditions

■ Accordingly, pursuant to the authority delegated to me by the Administrator, the following special conditions are issued as part of the type certification basis for the Mooney M20M and M20R airplanes modified by Garmin International, Inc., to add the GFC-700 autopilot system.

1. *Protection of Electrical and Electronic Systems from High Intensity Radiated Fields (HIRF).* Each system that performs critical functions must be designed and installed to ensure that the operations, and operational capabilities of these systems to perform critical functions, are not adversely affected when the airplane is exposed to high

intensity radiated electromagnetic fields external to the airplane.

2. For the purpose of these special conditions, the following definition applies: *Critical Functions:* Functions whose failure would contribute to, or cause, a failure condition that would prevent the continued safe flight and landing of the airplane.

Issued in Kansas City, Missouri on December 21, 2005.

**Kim Smith,**

*Manager, Small Airplane Directorate, Aircraft Certification Service.*

[FR Doc. 05-24668 Filed 12-29-05; 8:45 am]

**BILLING CODE 4910-13-P**

## DEPARTMENT OF TRANSPORTATION

### Federal Aviation Administration

#### 14 CFR Part 39

[Docket No. 2001-NE-02-AD; Amendment 39-14439; AD 2005-26-18]

**RIN 2120-AA64**

#### **Airworthiness Directives; Rolls-Royce Deutschland (Formerly Rolls-Royce plc) Models Tay 650-15 and 651-54 Turbofan Engines**

**AGENCY:** Federal Aviation Administration (FAA), DOT.

**ACTION:** Final rule.

**SUMMARY:** The FAA is superseding an existing airworthiness directive (AD) for Rolls-Royce Deutschland (formerly Rolls-Royce plc) (RRD) models Tay 650-15 and 651-54 turbofan engines. That AD currently requires borescope inspection of the high pressure compressor (HPC) stage 12 disc assembly to detect damage caused by HPC outlet guide vane (OGV) retaining bolt failure, and replacement of unserviceable parts with serviceable parts. That AD also requires as terminating action, the incorporation of a new design retention arrangement for the HPC OGV to prevent HPC OGV retaining bolt failure. This AD requires the same actions but extends the terminating action compliance time for Tay 650-15 engines. This AD also includes references to later revisions of two of the applicable RRD service bulletins (SBs). This AD results from RRD relaxing the terminating action compliance time for Tay 650-15 engines due to reassessment by RRD. We are issuing this AD to prevent an uncontained failure of the HPC stage 11/12 disc spacer, which could result in damage to the airplane.

**DATES:** This AD becomes effective February 3, 2006. The Director of the

Federal Register previously approved the incorporation by reference of certain publications listed in the regulations as of February 15, 2002 (67 FR 4652, January 31, 2002).

**ADDRESSES:** You can get the service information identified in this AD from Rolls-Royce Deutschland Ltd & Co KG, Eschenweg 11, 15827 Blankenfelde-Mahlow, Germany, telephone: 011 49 (0) 33-7086-1768, fax: 011 49 (0) 33-7086-3356.

You may examine the AD docket at the FAA, New England Region, Office of the Regional Counsel, 12 New England Executive Park, Burlington, MA. You may examine the service information, at the FAA, New England Region, Office of the Regional Counsel, 12 New England Executive Park, Burlington, MA.

#### **FOR FURTHER INFORMATION CONTACT:**

Jason Yang, Aerospace Engineer, Engine Certification Office, FAA, Engine and Propeller Directorate, 12 New England Executive Park, Burlington, MA 01803-5299; telephone (781) 238-7747; fax (781) 238-7199.

**SUPPLEMENTARY INFORMATION:** The FAA proposed to amend 14 CFR part 39 with a proposed airworthiness directive (AD). The proposed AD applies to RRD models Tay 650-15 and 651-54 turbofan engines. We published the proposed AD in the **Federal Register** on July 25, 2005 (70 FR 42515). That action proposed to require the same actions as AD 2002-01-29 but extends the terminating action compliance time for Tay 650-15 engines.

#### **Examining the AD Docket**

You may examine the AD Docket (including any comments and service information), by appointment, between 8 a.m. and 4:30 p.m., Monday through Friday, except Federal holidays. See **ADDRESSES** for the location.

#### **Comments**

We provided the public the opportunity to participate in the development of this AD. We received no comments on the proposal or on the determination of the cost to the public.

#### **Conclusion**

We have carefully reviewed the available data and determined that air safety and the public interest require adopting the AD as proposed.

#### **Costs of Compliance**

There are about 400 Tay 650-15 and 651-54 turbofan engines of the affected design in the worldwide fleet. We estimate that 105 engines installed on airplanes of U.S. registry will be affected by this AD. We also estimate that it will