

functions of the agency, including whether the information will have practical utility;

- Evaluate the accuracy of the agency's estimate of the burden of the proposed collection of information, including the validity of the methodology and assumptions used;
- Enhance the quality, utility, and clarity of the information to be collected; and
- Minimize the burden of the collection of information on those who are to respond, including through the use of appropriate automated, electronic, mechanical, or other technological collection techniques or other forms of information technology, e.g., permitting electronic submission of responses.

*Agency:* DOL–EBSA.

*Title of Collection:* Access to Multiemployer Plan Information.

*OMB Control Number:* 1210–0131.

*Affected Public:* Private Sector—businesses or other for-profits and not-for-profit institutions.

*Total Estimated Number of Respondents:* 2,826.

*Total Estimated Number of Responses:* 445,000.

*Total Estimated Annual Burden Hours:* 32,800.

*Total Estimated Annual Other Costs Burden:* \$526,000.

Dated: February 20, 2013.

**Michel Smyth,**

*Departmental Clearance Officer.*

[FR Doc. 2013–04333 Filed 2–25–13; 8:45 am]

**BILLING CODE 4510–29–P**

## DEPARTMENT OF LABOR

### Mine Safety and Health Administration

#### Petitions for Modification of Application of Existing Mandatory Safety Standards

**AGENCY:** Mine Safety and Health Administration, Labor.

**ACTION:** Notice.

**SUMMARY:** Section 101(c) of the Federal Mine Safety and Health Act of 1977 and 30 CFR Part 44 govern the application, processing, and disposition of petitions for modification. This notice is a summary of petitions for modification submitted to the Mine Safety and Health Administration (MSHA) by the parties listed below to modify the application of existing mandatory safety standards codified in Title 30 of the Code of Federal Regulations.

**DATES:** All comments on the petitions must be received by the Office of Standards, Regulations and Variances on or before March 28, 2013.

**ADDRESSES:** You may submit your comments, identified by “docket number” on the subject line, by any of the following methods:

1. *Electronic Mail:* [zzMSHA-comments@dol.gov](mailto:zzMSHA-comments@dol.gov). Include the docket number of the petition in the subject line of the message.

2. *Facsimile:* 202–693–9441.

3. *Regular Mail or Hand Delivery:* MSHA, Office of Standards, Regulations and Variances, 1100 Wilson Boulevard, Room 2350, Arlington, Virginia 22209–3939, Attention: George F. Triebisch, Director, Office of Standards, Regulations and Variances. Persons delivering documents are required to check in at the receptionist's desk on the 21st floor. Individuals may inspect copies of the petitions and comments during normal business hours at the address listed above.

MSHA will consider only comments postmarked by the U.S. Postal Service or proof of delivery from another delivery service such as UPS or Federal Express on or before the deadline for comments.

#### FOR FURTHER INFORMATION CONTACT:

Barbara Barron, Office of Standards, Regulations and Variances at 202–693–9447 (Voice), [barron.barbara@dol.gov](mailto:barron.barbara@dol.gov) (Email), or 202–693–9441 (Facsimile). [These are not toll-free numbers.]

#### SUPPLEMENTARY INFORMATION:

##### I. Background

Section 101(c) of the Federal Mine Safety and Health Act of 1977 (Mine Act) allows the mine operator or representative of miners to file a petition to modify the application of any mandatory safety standard to a coal or other mine if the Secretary of Labor determines that:

(1) An alternative method of achieving the result of such standard exists which will at all times guarantee no less than the same measure of protection afforded the miners of such mine by such standard; or

(2) That the application of such standard to such mine will result in a diminution of safety to the miners in such mine.

In addition, the regulations at 30 CFR 44.10 and 44.11 establish the requirements and procedures for filing petitions for modification.

##### II. Petitions for Modification

*Docket No:* M–2013–005–C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222–1000.

*Mine:* Francisco Mine Underground Pit, MSHA I.D. No. 12–02295, located in Gibson County, Indiana.

*Regulation Affected:* 30 CFR 75.500(d) (Permissible electric equipment).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in or inby the last open crosscut, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining by its nature and size, and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment in or inby the last open crosscut.

(e) Nonpermissible surveying equipment will not be used if methane

is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn outby the last open crosscut.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air outby the last open crosscut.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M-2013-006-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Francisco Mine Underground Pit, MSHA I.D. No. 12-02295, located in Gibson County, Indiana.

*Regulation Affected:* 30 CFR 75.507-1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in return airways, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that

accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in return airways will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment in return airways.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn out of the return airways.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air out of the return.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M-2013-007-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Francisco Mine Underground Pit, MSHA I.D. No. 12-02295, located in Gibson County, Indiana.

*Regulation Affected:* 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment within 150 feet of pillar workings, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary. To ensure the safety of the miners in active mines and to protect miners in future mines that may mine in close proximity to these same active mines, it is necessary to determine the exact location and extent of the mine workings.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining by its nature and size, and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating

condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment within 150 feet of pillar workings.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn further than 150 feet from pillar workings.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket No:* M–2013–008–C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222–1000.

*Mine:* Gateway Mine, MSHA I.D. No. 11–02408, located in Randolph County, Illinois.

*Regulation Affected:* 30 CFR 75.500(d) (Permissible electric equipment).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in or inby the last open crosscut, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible

surveying equipment in or inby the last open crosscut.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn outby the last open crosscut.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air outby the last open crosscut.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M–2013–009–C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222–1000.

*Mine:* Gateway Mine, MSHA I.D. No. 11–02408, located in Randolph County, Illinois.

*Regulation Affected:* 30 CFR 75.507–1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in return airways, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in return airways will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment in return airways.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn out of the return airways.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air out of the return.

(h) Qualified personnel who use surveying equipment will be properly

trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M-2013-010-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Gateway Mine, MSHA I.D. No. 11-02408, located in Randolph County, Illinois.

*Regulation Affected:* 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment within 150 feet of pillar workings, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary. To ensure the safety of the miners in active mines and to protect miners in future mines that may mine in close proximity to these same active mines, it is necessary to determine the exact location and extent of the mine workings.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used within

150 feet of pillar workings will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment within 150 feet of pillar workings.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn further than 150 feet from pillar workings.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket No:* M-2013-011-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Wildcat Hills Underground Mine, MSHA I.D. No. 11-03156, located in Saline County, Illinois.

*Regulation Affected:* 30 CFR 75.500(d) (Permissible electric equipment).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in or inby the last open crosscut, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in or inby the last open crosscut will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment in or inby the last open crosscut.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn outby the last open crosscut.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air outby the last open crosscut.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M-2013-012-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Wildcat Hills Underground Mine, MSHA I.D. No. 11-03156, located in Saline County, Illinois.

*Regulation Affected:* 30 CFR 75.507-1(a) (Electric equipment other than power-connection points; outby the last open crosscut; return air; permissibility requirements).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment in return airways, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps

in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used in return airways will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment in return airways.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn out of the return airways.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air out of the return.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all times guarantee no less than the same measure of protection as that afforded by the existing standard.

*Docket Number:* M-2013-013-C.

*Petitioner:* Peabody Midwest Mining, LLC, Three Gateway Center, Suite 1500, 401 Liberty Avenue, Pittsburgh, Pennsylvania 15222-1000.

*Mine:* Wildcat Hills Underground Mine, MSHA I.D. No. 11-03156, located in Saline County, Illinois.

*Regulation Affected:* 30 CFR 75.1002(a) (Installation of electric equipment and conductors; permissibility).

*Modification Request:* The petitioner requests a modification of the existing standard to permit an alternative method of compliance to allow the use of battery-powered nonpermissible surveying equipment within 150 feet of pillar workings, including, but not limited to, portable battery-operated mine transits, total station surveying equipment, distance meters, and data loggers. The petitioner states that:

(1) To comply with requirements for mine ventilation maps and mine maps in 30 CFR 75.372 and 75.1200, use of the most practical and accurate surveying equipment is necessary. To ensure the safety of the miners in active mines and to protect miners in future mines that may mine in close proximity to these same active mines, it is necessary to determine the exact location and extent of the mine workings.

(2) Application of the existing standard would result in a diminution of safety to the miners. Underground mining, by its nature and size and the complexity of mine plans, requires that accurate and precise measurements be completed in a prompt and efficient manner. The petitioner proposes the following as an alternative to the existing standard:

(a) Nonpermissible electronic surveying equipment may be used. Such nonpermissible surveying equipment includes portable battery-operated total

station surveying equipment, mine transits, distance meters, and data loggers.

(b) All nonpermissible electronic surveying equipment to be used within 150 feet of pillar workings will be examined by surveying personnel prior to use to ensure the equipment is being maintained in a safe operating condition. These examinations will include the following steps:

(i) Checking the instrument for any physical damage and the integrity of the case.

(ii) Removing the battery and inspecting for corrosion.

(iii) Inspecting the contact points to ensure a secure connection to the battery.

(iv) Reinserting the battery and powering up and shutting down to ensure proper connections.

(v) Checking the battery compartment cover to ensure that it is securely fastened.

(c) The results of such examinations will be recorded and retained for one year and made available to MSHA on request.

(d) A qualified person as defined in 30 CFR 75.151 will continuously monitor for methane immediately before and during the use of nonpermissible surveying equipment within 150 feet of pillar workings.

(e) Nonpermissible surveying equipment will not be used if methane is detected in concentrations at or above one percent for the area being surveyed. When methane is detected at such levels while the nonpermissible surveying equipment is being used, the equipment will be deenergized immediately and the nonpermissible electronic equipment withdrawn further than 150 feet from pillar workings.

(f) All hand-held methane detectors will be MSHA-approved and maintained in permissible and proper operating condition as defined in 30 CFR 75.320.

(g) Batteries in the surveying equipment will be changed out or charged in fresh air more than 150 feet from pillar workings.

(h) Qualified personnel who use surveying equipment will be properly trained to recognize the hazards associated with the use of nonpermissible surveying equipment in areas where methane could be present.

(i) The nonpermissible surveying equipment will not be put into service until MSHA has initially inspected the equipment and determined that it is in compliance with all the terms and conditions in this petition.

The petitioner asserts that the proposed alternative method will at all

times guarantee no less than the same measure of protection as that afforded by the existing standard.

Dated: February 21, 2013.

**George F. Triebsch,**

*Director, Office of Standards, Regulations and Variances.*

[FR Doc. 2013-04370 Filed 2-25-13; 8:45 am]

**BILLING CODE 4510-43-P**

## LIBRARY OF CONGRESS

### United States Copyright Office

[Docket No. 2011-10]

### Remedies for Small Copyright Claims: Third Request for Comments

**AGENCY:** U.S. Copyright Office, Library of Congress.

**ACTION:** Notice of inquiry.

**SUMMARY:** The United States Copyright Office is requesting public comment for the third time on the topic of adjudicating small copyright claims. The Office is studying whether and, if so, how the current legal system hinders or prevents copyright owners from pursuing copyright claims that have a relatively small economic value and will discuss, with appropriate recommendations, potential changes in administrative, regulatory, and statutory authority. At this time, the Office seeks additional comments on possible alternatives to the current system to improve the adjudication of such claims.

**DATES:** Comments are due April 12, 2013.

**ADDRESSES:** All comments are to be submitted electronically. A comment page containing a comment form is posted on the Office Web site at <http://www.copyright.gov/docs/smallclaims>. The Web site interface requires commenting parties to complete a form specifying name and organization, as applicable, and to upload comments as an attachment via a browser button. To meet accessibility standards, commenting parties must upload comments in a single file not to exceed six megabytes (MB) in one of the following formats: The Adobe Portable Document File (PDF) format that contains searchable, accessible text (not an image); Microsoft Word; WordPerfect; Rich Text Format (RTF); or ASCII text file format (not a scanned document). The form and face of the comments must include both the name of the submitter and organization. The Office will post the comments publicly on the Office's Web site exactly as they